

MANUFACTURE STANDARD, MANUFACTURE RELIANCE

RT- 3100 Microplate Washer



WHAT'S NEW

MULTI-CHANNEL

PLATE SHAKING

BUILD-IN INCUBATOR



Features

- Fully automatic
- User friendly operation system with large LCD display
- Washes flat, U and V-bottom strips and plate
- 12-way or 8-way manifold, automatic and manual positioning
- Large memory, up to 100 wash protocols can be programmed
- Multi-channel, 1or 3 (optional) for wash, 1 for rinse and 1 for waste
- Plate shaking function, time and speed are adjustable
- Two 96-well plate incubation positions (optional)
- Liquid level detection and alert function
- Easy maintenance





RT-3100

Microplate Washer



Main screen of the system

Version: 1,0	SN; 1234567890
Plate washing	Plate settings
ASPR/DISP	Switch bottle
PRIME	Adv. settings
RINSE	Switch off

Plate washing parameters

Program	No.: 1	Setting	gs
1 (12-F)	Plate	12-Pin	350uL
1#, 3Time	is.	BW-N/B	W-Y
Single /De	ouble	Asp 2.0/	3.0 s
Soak 10/1	158	Shk10/1	5s
*ST	ART to	ont. "CAN	ICEL"

Plate washing status

Program No.: 1	1/3
Strip No.: 8	
Position:	
Dispensing	80%

Advanced settings screen

Contrast ratio settings
Hang-up settings
Stroke settings
Incubator



Internal incubator (optional)

- Smart design
- Easy to use



Main Specifications

Plate Mode	96-/48-well plate or strip	
Residual Volume	<1µI	
Washing Volume	10~3000µl/well, 1µl by step	
Washing Cycle	Maximum 99 cycles	
Strip Washing	1 to 12 strips programmable	
Soaking Time	0~24hours	
Shaking Time	0~24hours	
Display	Large LCD	
Wash Channels	5 channels, 1 or 3 (optional) for wash, 1 for	
	rinse and 1 for waste	
Memory	100 washing protocols	
Interface	RS-232	
Power Supply	AC 110/220V±10%, 50~60HZ	
Net Weight	13 Kg	
Dimension	450MM×390MM×190MM	

Rayto Life and Analytical Sciences Co.,Ltd.

2nd Floor, 5th Building,Software Park,Kejizhong 2nd Road,High-tech Industrial Park,Nanshan, Shenzhen 518057,P.R.China Tel:+86(755)88832350 86168182 Fax:+86(755)86168796

Email:info@rayto.com

